



Domestic dehumidifiers that are compact, portable and easy to move and setup. Available in 3 versions, according to dehumidification capacity: 12L, 16L and 20L.

Features

Super-silent rotary compressor.
Electronic humidistat, allowing you to select the required level of humidity, and ambient humidity indicator.
2 speeds and 3 operating modes: MANUAL, CONTINUOUS & AUTOMATIC. Automatic mode will select the level of humidity based on the ambient temperature.
Programmable 1-24 hour run-on timer.
Anti-frost function: activates when the ambient temperature falls below approximately 15°C.
Automatic reset in the event of a power cut.
Automatic shut-off function: activates when the water tank is full.



Control panel.



Wheels.



Easy-clean air filter.



Continuous water drainage device.



Removable 2L water tank.

TECHNICAL CHARACTERISTICS

Model	Voltage 50Hz (V)	Power (W)	Absorbed current (A)	Sound power level (dB(A))	Dehumidification capacity (litres/24H.) (30°C/80 R.H.)	Surface area of influence* (m²)	Operating temperature	Electronic humidistat	Speeds	Automatic anti-frost function	Full tank indicator	Water drainage connection	Impurities filter	Carrying handles	Coolant	Colour	Weight (kg)	Wiring diagram** (n°)
DHUM-12 E	230	260	1,2	40	12	30	5 - 32°C	•	2	•	•	•	•	•	R134A	White RAL 9003 / Black RAL 9005	11,2	36
DHUM-16 E	230	410	1,8	42	16	40	5 - 32°C	•	2	•	•	•	•	•	R134A	White RAL 9003 / Black RAL 9005	13,2	36
DHUM-20 E	230	480	2,1	42	20	45	5 - 32°C	•	2	•	•	•	•	•	R134A	White RAL 9003 / Black RAL 9005	13,7	36

Dimensions LxWxH (mm): 365x220x490

* Information provided as guidance for ceiling heights of 2.5 m.

** See section of Wiring Diagrams.