



SL-2008

Warm air hand dryers, security device to avoid continued function if an object is left below.  
Fitted with thermal overload protection in the motor and the heating element.



SL-2008 AUTOMATIC



SL-2008 SILVER  
AUTOMATIC

#### TECHNICAL CHARACTERISTICS

Model	Voltage (V) 50 Hz	Maximum power absorbed (W)	Current (A)	Maximum airflow (m <sup>3</sup> /h)	Air speed (m/s)	Insulation/Protection	Sound pressure level* (dB(A))	Casing material	On	Off	Dimensions LxWxH (mm)	Weight (kg)	Colour	Electric scheme**
SL-2008	230	1875	8,5	170	17	Class II / IPX1	52	Polycarbonate	Push button	Run-On-Timer 45s	212x155x332	2,8	White	37
SL-2008 AUTOMATIC	230	1875	8,5	170	17	Class II / IPX1	52	Polycarbonate	Infra-red	When the hands are removed	212x155x332	2,8	White	37
SL-2008 SILVER AUTOMATIC	230	1875	8,5	170	17	Class II / IPX1	52	Polycarbonate	Infra-red	When the hands are removed	212x155x332	2,8	Silver	37

\* Sound pressure level measured at 1,5 m at free air conditions.

\*\* See section Electric Schemes.